



Conveyor & Storage Solutions, Inc.

(877) 227-7235

WWW.CSSYES.COM

Optimizing Your Warehouse for Success

FPS400LPA
FOX PACKAGING SERVICES



FPS 400LPA SPECIFICATIONS:

| | |
|---------------------------|--|
| PRODUCTION SPEED | 1-40 LPH* |
| LOAD SIZE | 55"L x 55"W x 91"H (80" Diagonal) |
| WEIGHT CAPACITY | 5000LBS |
| STRUCTURAL | WELDED STEEL CONSTRUCTION |
| TURNTABLE DRIVE | 1/2HP SCR DRIVE, 20:1 GEARBOX 32 TABLE SUPPORT WHEELS |
| TURNTABLE SPEED | 0-15RPM |
| CARRIAGE DRIVE | 1/2HP SCR DRIVE, #50 ANSI CHAIN |
| FILM DELIVERY | HURRICANE PRESTRETCH CARRIAGE |
| FILM ROLL | 20" MACHINE FILM, 3" CORE |
| POWER REQUIREMENTS | 115VAC, 15A, 60Hz- PLUG AND PLAY |

| | |
|-------------------------|---|
| ONBOARD PROGRAMS | STANDARD WRAP CYCLE STD W/TOP COVER PAUSE BOTTOM WRAPS FIRST WRAP UPWARDS ONLY |
|-------------------------|---|

| | |
|----------------|--|
| OPTIONS | <ul style="list-style-type: none"> • HEIGHT/BASE EXTENSION • LOADING RAMP • COMBINATION RAMP- FOR POWERED HAND TRUCKS • INTEGRATED SCALE PACKAGE |
|----------------|--|

*Loads Per Hour- May vary depending on load sizes, loading/unloading speeds, and number of wraps or wrapping pauses on load.

FULL SPECIFICATIONS:

CONTROL FEATURES:

- PLC full color touch screen display
- LCD Display Screen (providing function control viewing)
- Variable Turntable Speed 0-15 RPM
- Variable Film Carriage Speed Up/Down Control
- Separate Top/Bottom Wrap Selectors 1-9
- Separate Film Height Selector 1-9"
- Flush Mounted Control Panel (built into tower)
- Cycle Counter
- Manual Carriage Raise/Lower Control
- Turntable Jog with Auto Home Alignment
- Large Emergency push button power On / Off Switch with indicator light
- Start Cycle Push Button
- Standard Wrap Up/Down Program
- 12 Volt DC Control System (for operator safety)
- All circuits protected by fuses (easy access)
- 20 amp Power Board Circuits to carry a 10 amp load

FILM DELIVERY SYSTEM:

- HURRICANE THREAD 20" prestretch film delivery system
- 200% factory set stretch (50-250% available upon request)
- Easy thread film carriage
- No hinges, latches or idler rollers to wear and cause inconsistent film stretching
- Electronic film force control on panel
- Adjustable mechanical force to load
- Linear analog proximity sensor film feed speed control
- 1/2 HP DC SCR variable speed film drive
- Triple beam auto height eye capable of recognizing all colors including black

CARRIAGE LIFT:

- UHMW supports providing effortless movement and maximum stability (Qty4)
- Heavy duty ANSI #50 chain carriage lift
- 1/2 HP DC SCR variable speed drive
- Carriage chain fully guarded

TURNTABLE DRIVE:

- 0-15 RPM Table Speed
- 1/2 HP SCR variable speed
- Adjustable electronic soft start / stop
- Positive home position alignment
- Safety E-Stop button
- 40 table support wheels